

- {W:\05677\0202587-us0\01133049.DOC [PRINTED BY THE NATIONAL ARCHIVES AND RECORDS SERVICE]}

6. (Currently Amended) The vehicle wheel of claim 1, wherein the thin, deformable part is positioned so that side edge portions of the disk ~~radial portion spoke~~ on either side of the thin, deformable part are visible and extend radially outward from side edges of the thin, deformable part.
7. (Currently Amended) The vehicle wheel of claim 1, wherein the deformable narrow spoke portion covers less than the entire surface of the disk ~~radial portion spoke~~.
8. (Currently Amended) A vehicle wheel comprising:  
a wheel base unit having a rim portion and a disk portion, the disk portion including a hub attachment portion to be attached to an axle and a disk ~~radial portion spoke~~ interconnecting the rim portion and the hub attachment portion; and  
a cover attached to the wheel base unit portion, the cover including a deformable narrow spoke ~~portions portion~~ for partially covering the disk ~~radial portions spoke~~ along a radial direction of the wheel while leaving part of the disk ~~radial portions spoke~~ exposed,  
wherein the deformable narrow spoke ~~portions include portion~~ includes thin deformable parts covering approximately a middle part of the disk ~~radial portions spoke~~, and  
wherein the thin, deformable parts have a smaller height in comparison with the rest of the deformable narrow spoke portions.